

MEE5114 Advanced Control for Robotics

Lecture 3: Operator View of Rigid-Body Transformation

Prof. Wei Zhang

SUSTech Institute of Robotics
Department of Mechanical and Energy Engineering
Southern University of Science and Technology, Shenzhen, China

Outline

- Rotation Operation via Differential Equation
- Rotation Operation in Different Frames
- Rigid-Body Operation via Differential Equation
- Homogeneous Transformation Matrix as Rigid-Body Operator
- Rigid-Body Operation of Screw Axis

Outline

- Rotation Operation via Differential Equation
- Rotation Operation in Different Frames
- Rigid-Body Operation via Differential Equation
- Homogeneous Transformation Matrix as Rigid-Body Operator
- Rigid-Body Operation of Screw Axis

Skew Symmetric Matrices

- Recall that cross product is a special linear transformation.
- For any $\omega \in \mathbb{R}^n$, there is a matrix $[\omega] \in \mathbb{R}^{n \times n}$ such that $\omega \times p = [\omega]p$

$$\omega = \begin{bmatrix} \omega_1 \\ \omega_2 \\ \omega_3 \end{bmatrix} \leftrightarrow [\omega] = \begin{bmatrix} 0 & -\omega_3 & \omega_2 \\ \omega_3 & 0 & -\omega_1 \\ -\omega_2 & \omega_1 & 0 \end{bmatrix}$$

- Note that $[\omega] = -[\omega]^T \leftarrow$ skew symmetric
- $[\omega]$ is called a skew-symmetric matrix representation of the vector ω
- The set of skew-symmetric matrices in: $so(n) \triangleq \{S \in \mathbb{R}^{n \times n} : S^T = -S\}$
- We are interested in case $n = 2, 3$

Rotation Operation via Differential Equation

- Consider a point initially located at p_0 at time $t = 0$
- Rotate the point with unit angular velocity $\hat{\omega}$. Assuming the rotation axis passing through the origin, the motion is described by

$$\dot{p}(t) = \hat{\omega} \times p(t) = [\hat{\omega}]p(t), \text{ with } p(0) = p_0 \quad (1)$$

- This is a linear ODE with solution: $p(t) = e^{[\hat{\omega}]t}p_0$
- After $t = \theta$, the point has been rotated by θ degree. Note $p(\theta) = e^{[\hat{\omega}]\theta}p_0$
- $\text{Rot}(\hat{\omega}, \theta) \triangleq e^{[\hat{\omega}]\theta}$ can be viewed as a rotation operator that rotates a point about $\hat{\omega}$ through θ degree

Rotation Matrix as a Rotation Operator (1/3)

- Every rotation matrix R can be written as $R = \text{Rot}(\hat{\omega}, \theta) \triangleq e^{[\hat{\omega}]\theta}$, i.e., it represents a rotation operation about $\hat{\omega}$ by θ .
- We have seen how to use R to represent frame orientation and change of coordinate between different frames. They are quite different from the operator interpretation of R .
- To apply the rotation operation, all the vectors/matrices have to be expressed in the **same reference frame** (this is clear from Eq (1))

Rotation Matrix as a Rotation Operator (2/3)

- For example, assume $R = \begin{bmatrix} 1 & 0 & 0 \\ 0 & 0 & -1 \\ 0 & 1 & 0 \end{bmatrix} = \text{Rot}(\hat{x}; \pi/2)$
- Consider a relation $q = Rp$:
 - **Change reference frame interpretation :**

 - **Rotation operator interpretation:**

Rotation Matrix as a Rotation Operator (3/3)

- Consider the frame operation:
 - Change of reference frame: $R_B = RR_A$

- Rotating a frame: $R'_A = RR_A$

Outline

- Rotation Operation via Differential Equation
- Rotation Operation in Different Frames
- Rigid-Body Operation via Differential Equation
- Homogeneous Transformation Matrix as Rigid-Body Operator
- Rigid-Body Operation of Screw Axis

Rotation Matrix Properties

- $R^T R = I$
- $R_1 R_2 \in SO(3)$, if $R_1, R_2 \in SO(3)$
- $\|Rp - Rq\| = \|p - q\|$
- $R(v \times w) = (Rv) \times (Rw)$
- $R[w]R^T = [Rw]$

Rotation Operator in Different Frames (1/2)

- Consider two frames $\{A\}$ and $\{B\}$, the actual numerical values of the operator $\text{Rot}(\hat{\omega}, \theta)$ depend on both the reference frame to represent $\hat{\omega}$ and the reference frame to represent the operator itself.
- Consider a rotation axis $\hat{\omega}$ (coordinate free vector), with $\{A\}$ -frame coordinate ${}^A\hat{\omega}$ and $\{B\}$ -frame coordinate ${}^B\hat{\omega}$. We know

$${}^A\hat{\omega} = {}^B R_A {}^B\hat{\omega}$$

- Let ${}^B\text{Rot}({}^B\hat{\omega}, \theta)$ and ${}^A\text{Rot}({}^A\hat{\omega}, \theta)$ be the two rotation matrices, representing the same rotation operation $\text{Rot}(\hat{\omega}, \theta)$ in frames $\{A\}$ and $\{B\}$.

Rotation Operator in Different Frames (2/2)

- We have the relation:

$${}^A\text{Rot}({}^A\hat{\omega}, \theta) = {}^A R_B {}^B\text{Rot}({}^B\hat{\omega}, \theta) {}^B R_A$$

Outline

- Rotation Operation via Differential Equation
- Rotation Operation in Different Frames
- **Rigid-Body Operation via Differential Equation**
- Homogeneous Transformation Matrix as Rigid-Body Operator
- Rigid-Body Operation of Screw Axis

Rigid-Body Operation via Differential Equation (1/3)

- Recall: Every $R \in SO(3)$ can be viewed as the state transition matrix associated with the rotation ODE(1). It maps the initial position to the current position (after the rotation motion)
 - $p(\theta) = \text{Rot}(\hat{\omega}, \theta)p_0$ viewed as a solution to $\dot{p}(t) = [\hat{\omega}]p(t)$ with $p(0) = p_0$ at $t = \theta$.
 - The above relation requires that the rotation axis passes through the origin.
- We can obtain similar ODE characterization for $T \in SE(3)$, which will lead to exponential coordinate of $SE(3)$

Rigid-Body Operation via Differential Equation (2/3)

- Recall: Theorem (Chasles): Every rigid body motion can be realized by a screw motion
- Consider a point p undergoes a screw motion with screw axis \mathcal{S} and unit speed ($\dot{\theta} = 1$). Let the corresponding twist be $\mathcal{V} = \mathcal{S} = (\omega, v)$. The motion can be described by the following ODE.

$$\dot{p}(t) = \omega \times p(t) + v \quad \Rightarrow \quad \begin{bmatrix} \dot{p}(t) \\ 0 \end{bmatrix} = \begin{bmatrix} [\omega] & v \\ 0 & 0 \end{bmatrix} \begin{bmatrix} p(t) \\ 1 \end{bmatrix} \quad (2)$$

- Solution to (2) in homogeneous coordinate is:

$$\begin{bmatrix} p(t) \\ 1 \end{bmatrix} = \exp \left(\begin{bmatrix} [\omega] & v \\ 0 & 0 \end{bmatrix} t \right) \begin{bmatrix} p(0) \\ 1 \end{bmatrix}$$

Rigid-Body Operation via Differential Equation (3/3)

- For any twist $\mathcal{V} = (\omega, v)$, let $[\mathcal{V}]$ be its matrix representation

$$[\mathcal{V}] = \begin{bmatrix} [\omega] & v \\ 0 & 0 \end{bmatrix}$$

- The above definition also applies to a screw axis $\mathcal{S} = (\omega, v)$
- With this notation, the solution to (2) is $\tilde{p}(t) = e^{[\mathcal{S}]t}\tilde{p}(0)$
- Fact: $e^{[\mathcal{S}]t} \in SE(3)$ is always a valid homogeneous transformation matrix.
- Fact: Any $T \in SE(3)$ can be written as $T = e^{[\mathcal{S}]t}$, i.e., it can be viewed as an operator that moves a point/frame along the screw axis at unit speed for time t

$se(3)$

- Similar to $so(3)$, we can define $se(3)$:

$$se(3) = \{([\omega], v) : [\omega] \in so(3), v \in \mathbb{R}^3\}$$

- $se(3)$ contains all matrix representation of twists or equivalently all twists.
- In some references, $[\mathcal{V}]$ is called a twist.
- Sometimes, we may abuse notation by writing $\mathcal{V} \in se(3)$.

Outline

- Rotation Operation via Differential Equation
- Rotation Operation in Different Frames
- Rigid-Body Operation via Differential Equation
- **Homogeneous Transformation Matrix as Rigid-Body Operator**
- Rigid-Body Operation of Screw Axis

Homogeneous Transformation as Rigid-Body Operator

- ODE for rigid motion under $\mathcal{V} = (\omega, v)$

$$\dot{p} = v + \omega \times p \quad \Rightarrow \quad \dot{\tilde{p}}(t) = \begin{bmatrix} [\omega] & v \\ 0 & 0 \end{bmatrix} \tilde{p}(t) \Rightarrow \tilde{p}(t) = e^{[\mathcal{V}]t} \tilde{p}(0)$$

- Consider “unit velocity” $\mathcal{V} = \mathcal{S}$, then time t means degree
- $\tilde{p}' = T\tilde{p}$: “rotate” p about screw axis \mathcal{S} by θ degree
- TT_A : “rotate” $\{A\}$ -frame about \mathcal{S} by θ degree

Rigid-Body Operator in Different Frames

- Expression of T in another frame (other than $\{O\}$):

$$\begin{array}{ccc} T & \leftrightarrow & T_B^{-1} T T_B \\ \text{operation in } \{O\} & & \text{operation in } \{B\} \end{array}$$

Outline

- Rotation Operation via Differential Equation
- Rotation Operation in Different Frames
- Rigid-Body Operation via Differential Equation
- Homogeneous Transformation Matrix as Rigid-Body Operator
- Rigid-Body Operation of Screw Axis

Rigid Operation on Screw Axis

- Consider an arbitrary screw axis \mathcal{S} , suppose the axis has gone through a rigid transformation $T = (R, p)$ and the resulting new screw axis is \mathcal{S}' , then

$$\mathcal{S}' = [\text{Ad}_T] \mathcal{S}$$

proof:

More Space